

Monsher Hose Reels



Hose Reel Conforming to BS EN671-1

- 1 Both wall-mounted and cabinet mounted available.
- 2 Steel waterway which will never rot. We use nipples not hose clamps, to fill in the interface between hose and waterway. Once being screwed tightly, no leakage.
- 3 Hose reel with powder coated and MS with RAL3000 & anti-ultraviolet powder coated side discs. There can be pressure gauge at the reel axis.
- 4 Maximum working pressure 12 kg and minimum burst pressure 30 kg.
- 5 Endurance test on reel rotation: After over 3000 rotation, hose reels show no visible leakage.
- 6 Swinging hose reels shall be able to swing 1000 times to minimum 170° and also show no visible leakage or damage
- 7 High Pressure spray. Reinforced nylon material, the nozzle can be adjusted to jet/spray.
- 8 Fire Hose : Black toothed with red strip, conforming to EN694 standard.



Model No.	Type	Hose Diameter & Length	Reel Height (A in mm)	Reel Width (B in mm)	Reel Depth (C in mm)	Min. Cabinet Size (W x H x D) in mm
CSJR-16-A	Manual & Swinging	19 mm x 30m	460	509	246	600 x 650 x 260

NOZZLE

Model No.	Setting	Nozzle diameter	Inlet size	Flow rate at 2 bar/ 6 bar (L/Min/Jet/Spray)	Throw range at 2 bar
N-04-2	Jet / Spray	6 mm	3/4"(19mm)	> 24/42	>11.2



Monsher (India) Safety Equipments Pvt. Ltd.

403 Tantia Jogani Estate, Off N M Joshi Road, Next to Lodha Pavilion, Lower Parel, Mumbai 400 011 (India)

T: +91 22 4051 2000 (30 Lines) F: +91 22 4051 2025 / 26 Email: productsales@monsher.com www.monsher.com